

VISCOCER® 1022

Product description **oxidised polyethylene wax** **EINECS: polymer**

VISCOCER® 1022 is an oxidised polyethylene wax.

Parameter	Test method	Unit	Target value
Appearance	visual	-	almost white flakes
Density (23°C)	PN-EN ISO 1183-1	g/cm ³	0.97
Drop point	ASTM D3954-94	°C	112
Viscosity (140°C)	PN-EN ISO 3219	mPa·s	525
Penetration (25°C)	DIN 51579	mm·10 ⁻¹	1
Acid value	PN-EN ISO 2114	mg(KOH)/g	22

Major fields of application

VISCOCER® 1022 is used in different kinds of technical applications, e.g. for manufacturing of water based wax emulsions. VISCOCER® 1022 is used as release agent for various applications.

Packaging

paper-bags of 20 kg netto
Palett of 1000 kg (50 bags)
Big bags of 750 kg netto

Storage

The product has to be stored dry at room temperature.
Beware of sunlight and heat.
Stability at least 2 years from date of delivery.

Hazards

This product does not require labelling in terms of preparation guideline. Further security relevant data see safety data sheet.

Ecology/toxicology properties

The product is water insoluble. Further information see material safety data sheet.

Status under food legislation

The product fulfills legislations of various countries. More details on request.

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

version 1.0 06.06.2024