

ADDIMER® 156

Product description	calcium ionomer	EINECS: polymer
ADDIMER [®] 156 is a calcium	containing ionomer.	
Characteristic	Unit	Target value
Appearance	-	white to off-white powder

mPa*s

~ 2800

Major fields of application

Viscosity (150°C)

ADDIMER[®] 156 is used as internal lubricant and nucleating agent in the processing of engineering plastics like PC, PA, PET and PBT. Typical dosage level is between 0.3 - 0.8 %.

Packaging

PE-bags of 20 kg netto Palett of 1000 kg (50 bags)

Storage

The product has to be stored dry at room temperature. Beware of sunlight and heat. Stability at least 2 years from date of delivery.

Hazards

This product does not require labelling in terms of CLP/GHS guideline. Further security relevant data see safety data sheet.

Ecology/toxicology properties

The product is water insoluble. Further information see material safety data sheet.

Status under food legislation

More details on request.

All information given here are based on our own research or the research of others and believed to be accurate and shall give the user guidance for the application. Nevertheless these data are no specification and due to the versatile possible formulations, applications, processings and further parameters at the formulator/user the usage of this product has to be tested carefully in the particular system/application by the formulator/user. All information mentioned here are not warranted properties. There is no responsibility of the seller if the material is used outside the recommended field of use; any liability, also for any patent infringement, cannot be derived from this.

version 0.1 24.07.2017

ceronas GmbH & Co. KG Hugo-Wagener-Str. 3 55481 Kirchberg / Germany Tel. +49 (0) 67 63/6 33 50-0 Fax +49 (0) 67 63/6 33 50 99

Geschäftsführer: Dr. Marco Puhl info@ceronas.de www.ceronas.de

Steuernummer: 40/208/02647 USt-IdNr.: DE284643559 Handelsregister: Amtsgericht Bad Kreuznach HRA: 20573 Pers. haftende Gesellschaft: ceronas Verwaltungs GmbH Amtsgericht Bad Kreuznach HRB: 21473 DMSZ zertifiziert nach DIN EN ISO 9001 22122 Z2122 Z2122 Z2122